



Cubic Stainless Steel Tanks for DEF

UM5.SSU Single Wall, Not-Insulated

UM5.SDU Double Wall, Not-Insulated

UM5.SDI Double Wall, Insulated

- Cubic Stainless Steel DEF Tanks
- Accessories: Vent Caps, Direct Read Gauge, Inspect Port, Fill, Suction Pipe and Return Fittings
- C1 Tank Monitor Panel with High, Low, Leak Alarm, Output Relays, 4-20mA Analog Transmitter and Leak Sensor

The UM5 Tank is a compact storage tank for DEF used in and around generator enclosures. The tank system can be equipped with pumps and controls to provide a complete DEF supply system for generator SCR emissions control.



Tank Specification	Stainless Steel Cubic Tank
Controller	C1 Control Panel
Power	120-230 VAC, 1P, 50-60 Hz
Interface	Power ON Light Analog Level Display Alarm Light Hi-Lo-Leak Modbus to BMS
Standard Accessories	Vent Caps Level Indicator Gauge Port Analog Level Leak Sensor
Optional Accessories	Tank Insulation Tank Heater

Model	GAL	WxLxH IN	Liter	W.L.H CM
UM6.25	25	12x24x24	100	30.60.60
UM6.50	50	12x36x36	200	30.90.90
UM6.75	75	12x30x36	300	60.76.90
UM6.100	100	30x30x36	400	76.76.90

Add 2 IN (50) to each Dimension for Double Wall

Other Equipment	UM1 Simplex DEF Transfer Pumps UM2 Duplex DEF Transfer Pumps UM4 DEF Tank Fill System Temperature Sensors and Control
------------------------	--